



ROSTFREI  
Inox  
Stainless  
Steel

1.1

1.2

1.3

1.4

2

d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub> ≈ (arrested)	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>
22	M 6	20	73	82	22	13	5,5
24	M 6	20	88	97	22	13	5,5
25	M 6	20	98	107	22	13	5,5

2.1

**Specification**

- Handle  
Plastic  
Technopolymer (Polyamide PA)  
- temperature resistant up to 90 °C  
- black, matte finish  
- revolving

KT

- **GN 798.7**  
Retractable mechanism  
- Axle parts  
Steel 1.0718, blackened  
- Flat base  
Sintered Steel, blackened

- **GN 798.8**  
Retractable mechanism  
Stainless Steel  
- Axle parts AISI 303  
- Flat base  
Sintered Steel AISI 316

• *Stainless Steel characteristics* → Page 1489

• *Plastic characteristics* → Page 1483

• **RoHS compliant**

**Information**

Safety retractable handles GN 798.7 / GN 798.8 together with cranked handles and handwheels are suitable for applications where the handle must not remain in the operating position.

In order to bring the handle into the operating position it has to be turned first through 90° to a stop against a torsion spring and then it is pushed against spring pressure into its hold position.

By maintaining the forward thrust on the handle, the handwheel can easily be rotated.

When releasing the handle, the springs return it back to the retracted position.

2.2

2.3

2.4

How to order

**GN 798.8-KT-24**

1 **Material**

2 **d<sub>1</sub>**

