



2 Bore code
K with keyway

1 d ₁	3 d ₂ H7 Bore	4 l ₁ - l ₂				d ₃	l ₃ Guide length	l ₅	t +1 max. assembly length of the shaft	Permissible r.p.m. / torque / Selection of the size → Page 1143
22	K 10	140-30	160- 40	180- 60	-	22	30	48	12	
25	K 12	160-30	180- 45	200- 70	250-105	26	40	56	13	
28	K 14	170-30	200- 60	220- 80	280-140	29	40	60	13	
32	K 16	190-30	240- 80	275-115	380-210	32	40	68	16	
36	K 18	230-50	270-100	290-110	400-220	37	40	74	17	
42	K 20	250-50	320-120	420-220	-	42	45	82	18	
45	K 22	270-50	330-100	470-240	-	47	50	95	22	
50	K 25	295-50	350-100	420-170	-	52	50	108	26	
58	K 30	330-50	400-110	-	-	58	60	122	29	

Specification

- Steel blank
- Joint bearing areas, pins case hardened
- Keyway JS9 DIN 6885 → Page 1420
- Cross holes GN 110.1 → Page 1422
- ISO-Fundamental tolerances → Page 1479
- RoHS compliant

On request

- different length l₁ - l₂
- Bores without keyway
- Bores with square
- with other or unequal bores

Information

Universal joint shafts with needle bearing GN 808.3 not only join the offset between two shafts, but also enable the alignment of lengths, which depending on the overall length l₁ enables the corresponding extraction length l₂. The power transmission is achieved by two universal joints DIN 808 (type EW) a splined shaft and a sliding sleeve.

It is important to check the accuracy when connecting the splined shaft to the sliding sleeve.

The markings → ← have to be opposite to each other. Any kind of mis-connection leads to an inhomogeneous output and to a quick abrasion.

see also...

- Universal joints with friction bearing GN 808.2 → Page 1146

How to order	1 d ₁
	2 Bore code
GN 808.3-32-K 16-240-80	3 d ₂ (s)
	4 l ₁ - l ₂