


Examples of application



ROSTFREI
Inox
Stainless
Steel

1		2		3										d ₃	l ₂	l ₃	A/F
d ₁ f9	d ₂	l ₁ +0,25															
4	M 3	4	5	6	8	10	12	16	-	-	-	-	7	7	3	2	
5	M 4	5	6	8	10	12	16	20	25	30	-	-	9	8	4	2,5	
6	M 5	10	12	16	20	25	30	40	50	60	-	-	10	9,5	4,5	3	
8	M 6	16	20	25	30	40	50	60	-	-	-	-	13	11	5,5	4	
10	M 8	16	20	25	30	40	50	60	70	80	90	100	16	13	7	5	
12	M 10	16	20	25	30	40	50	60	70	80	90	100	18	16	9	6	
16	M 12	30	40	50	60	70	80	90	100	-	-	-	24	18	11	8	

Specification

- Stainless Steel - AISI 304 (A2)
- Adapter dimension d₁ ground
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS compliant

4

Information

Stainless Steel-Shoulder screws ISO 7379 are cost-saving construction elements for a wide variety of different uses.

The maximum tightening torque is limited by the relatively small bearing points (shoulders) and by the recesses at the transition point from d₁ to d₂ and d₁ to d₃.

Standard deviation:

- no information about the concentricity 2 IT 13 and 2 IT 10
- the official ISO standard sheet has the following dimensions for d₁ - d₂: 6,5-M5 / 13-M10 / 25-M20
- the dimensions 4-M3 and M4-M5 are not included in the official ISO standard sheet

How to order	1	d ₁
	2	d ₂
	3	l ₁
ISO 7379-10-M8-40-NI	4	Material