

外形寸法図

ハーフユニオン:KFH

(mm)




〈樹脂スリーブ〉



〈黄銅スリーブ〉

適用チューブ サイズ mm		接続 ねじ R	型式	六角対辺		L ₁	L ₂	M	ød	※A	有効 断面積 mm ²	質量g			
外径	内径			H ₁	H ₂										
ø4	ø2.5	R1/8	KFH04-01S	10	10	29.6	22.9	15.5	1.5	26.5	1.6	13			
		R1/4	KFH04-02S	14	14	34	27.3					23			
		R1/8	KFH04B-01S	10	10	26.5	23.5	12.4	1.5	23.4	1.6	14			
		R1/4	KFH04B-02S	14	14	30.9	27.9					24			
ø6	ø4	R1/8	KFH06-01S	10	12	29.3	22.6	15.2	3	26.2	6	14			
		R1/4	KFH06-02S	14	14	33.7	27					25			
		R3/8	KFH06-03S	17	17	34.1	27.4	12.2	3	28.9	6	36			
		R1/8	KFH06B-01S	10	10	26.3	23.3					15			
		R1/4	KFH06B-02S	14	14	30.7	27.7	12.2	3	25.2	6	26			
		R3/8	KFH06B-03S	17	17	31.1	28.1					25.9	37		
ø8	ø5	R1/8	KFH08U-01S	12	14	29.3	22.6	16.2	4	26.2	11	16			
		R1/4	KFH08U-02S	14	14	33.7	27					25			
		R3/8	KFH08U-03S	17	17	34.1	27.4					37			
	ø6	ø5	R1/8	KFH08N-01S	12	14	29.3	22.6	16.2	5	26.2	17	16		
			R1/4	KFH08N-02S	14	14	33.7	27					24		
			R3/8	KFH08N-03S	17	17	34.1	27.4					36		
		ø6	ø6	R1/8	KFH08B-01S	12	14	26.4	23.4	13.3	5	23.3	17	17	
				R1/4	KFH08B-02S	14	14	30.8	27.8					25.3	25
				R3/8	KFH08B-03S	17	17	31.2	28.2					26.0	37
	ø10	ø6.5	R1/4	KFH10U-02S	17	17	35.3	28	18.8	5.5	29.8	21	32		
			R3/8	KFH10U-03S	17	17	35.7	28.4					40		
			R1/2	KFH10U-04S	22	22	38.9	31.6					65		
ø7.5		ø6.5	R1/4	KFH10N-02S	17	17	35.3	28	18.8	6.5	29.8	30	31		
			R3/8	KFH10N-03S	17	17	35.7	28.4					39		
		ø7.5	ø7.5	R1/2	KFH10N-04S	22	22	38.9	31.6	15.0	6.5	31.6	30	64	
				R1/4	KFH10B-02S	17	17	31.5	28.5					26.0	33
ø7.5		ø7.5	R3/8	KFH10B-03S	17	17	31.9	28.9	15.0	6.5	26.7	30	41		
			R1/2	KFH10B-04S	22	22	35.1	32.1					27.8	66	
ø12		ø8	R1/4	KFH12U-02S	17	19	35.8	29	19.3	7	30.3	35	33		
	R3/8		KFH12U-03S	17	19	36.2	29.4	41							
	R1/2		KFH12U-04S	22	22	39.4	32.6	65							
	ø9	ø8	R1/4	KFH12N-02S	17	19	35.8	29	19.3	8	30.3	45	31		
			R3/8	KFH12N-03S	17	19	36.2	29.4					39		
		ø9	ø9	R1/2	KFH12N-04S	22	22	39.4	32.6	15.5	8	32.1	45	64	
				R1/4	KFH12B-02S	17	17	32.1	29.1					26.6	33
	ø9	ø9	R3/8	KFH12B-03S	17	17	32.5	29.5	15.5	8	27.3	45	41		
			R1/2	KFH12B-04S	22	22	35.7	32.6					28.4	66	



※Rねじのねじ込み後の参考寸法。