

KF Series

外形寸法図

ストレートユニオン:KFH

(mm)




〈樹脂スリーブ〉



〈黄銅スリーブ〉

適用チューブ サイズ mm		型式	六角対辺		L ₁	L ₂	M	ød	有効 断面積 mm ²	質量g
外径	内径		H ₁	H ₂						
ø4	ø2.5	KFH04-00	8	10	40.9	27.6	15.5	1.5	1.6	13
		KFH04B-00			34.7	28.8	12.4			14
ø6	ø4	KFH06-00	10	12	40.3	27	15.2	3	6	17
		KFH06B-00			34.3	28.4	12.2			19
ø8	ø5	KFH08U-00	12	14	41.3	28	16.2	4	11	23
		KFH08N-00			5	17	22			
	KFH08B-00	35.5						29.6	13	24
ø10	ø6.5	KFH10U-00	17	17	44.6	30	18.8	5.5	21	36
		KFH10N-00			6.5	30	39			
	KFH10B-00	37.0						31.0	15.0	
ø12	ø8	KFH12U-00	17	19	45.5	32	19.3	7	35	42
		KFH12N-00			8	45	41			
	KFH12B-00	38.1						32.2	15.5	44



※Rねじのねじ込み後の参考寸法。

チーズユニオン:KFT

(mm)



〈樹脂スリーブ〉



〈黄銅スリーブ〉

適用チューブ サイズ mm		型式	六角対辺		L ₁	L ₂	M	ød	有効 断面積 mm ²	質量g
外径	内径		H ₁	H ₂						
ø4	ø2.5	KFT04-00	10	10	27.5	20.8	15.5	1.5	1.6	33
		KFT04B-00			24.4	21.4	12.4			35
ø6	ø4	KFT06-00	10	12	27.2	20.5	15.2	3	6	37
		KFT06B-00			24.2	21.2	12.2			39
ø8	ø5	KFT08U-00	12	14	30.2	23.5	16.2	4	11	54
		KFT08N-00			5	17	53			
	KFT08B-00	27.3						24.3	13.3	56
ø10	ø6.5	KFT10U-00	12	17	31.8	24.5	18.8	5.5	21	65
		KFT10N-00			6.5	30	63			
	KFT10B-00	28.0						25.0	15.0	
ø12	ø8	KFT12U-00	14	19	34.3	27.5	19.3	7	35	89
		KFT12N-00			8	45	85			
	KFT12B-00	30.6						27.6	15.5	90

