

外形寸法図

スィベルエルボ:KFV

(mm)



〈樹脂スリーブ〉



〈黄銅スリーブ〉

適用チューブ サイズ mm		接続 ねじ R	型式	六角対辺				L ₁	L ₂	L ₃	※L ₄	M	ød	※A	有効 断面積 mm ²	質量 g
外径	内径			H ₁	H ₂	H ₃	H ₄									
ø4	ø2.5	R1/8	KFV04-01S	10	10	14	10	26	19.3	32.8	29.7	15.5	1.5	35.5	1.4	40
		R1/4	KFV04-02S				14			37.2	31.7			37.5		50
		R1/8	KFV04B-01S				10			32.8	29.7			35.5		41
		R1/4	KFV04B-02S				14			37.2	31.7			37.5		51
ø6	ø4	R1/8	KFV06-01S	10	12	14	10	25.7	19	32.8	29.7	15.2	3	36.6	5	42
		R1/4	KFV06-02S				14			37.2	31.7			38.6		52
		R3/8	KFV06-03S				17			37.6	32.4			39.3		64
		R1/8	KFV06B-01S				10			32.8	29.7			36.6		43
		R1/4	KFV06B-02S				14	37.2	31.7	38.6	53					
		R3/8	KFV06B-03S				17	37.6	32.4	39.3	65					
ø8	ø5	R1/8	KFV08U-01S	12	14	17	12	27.2	20.5	33.8	30.7	16.2	4	38.8	9.4	52
		R1/4	KFV08U-02S				14			38.2	32.7			40.8		61
		R3/8	KFV08U-03S				17			38.6	33.4			41.5		73
	ø6	R1/8	KFV08N-01S				12	24.3	21.3	33.8	30.7	13.3	5	38.8	14	57
		R1/4	KFV08N-02S				14			38.2	32.7			40.8		60
		R3/8	KFV08N-03S				17			38.6	33.4			41.5		72
		R1/8	KFV08B-01S				12			33.8	30.7			38.8		58
		R1/4	KFV08B-02S				14			38.2	32.7			40.8		61
		R3/8	KFV08B-03S				17			38.6	33.4			41.5		73
		ø10	ø6.5				R1/4			KFV10U-02S	14			17		19
R3/8	KFV10U-03S			22	40.6	35.4	45.2	81								
R1/2	KFV10U-04S			22	43.8	36.5	46.3	104								
ø7.5	R1/4		KFV10N-02S	17	25.0	22.0	40.2	34.7	15.0	6.5		44.5	25		72	
	R3/8		KFV10N-03S	22			40.6	35.4				45.2			80	
	R1/2		KFV10N-04S	22			43.8	36.5				46.3			104	
	R1/4		KFV10B-02S	17			40.2	34.7				44.5			73	
	R3/8		KFV10B-03S	22			40.6	35.4				45.2			81	
R1/2	KFV10B-04S	22	43.8	36.5	46.3	105										
ø12	ø8	R1/4	KFV12U-02S	17	19	22	17	30.3	23.5	41.2	35.7	19.3	7	46.7	30	92
		R3/8	KFV12U-03S				22			41.6	36.4			47.4		100
		R1/2	KFV12U-04S				22			44.8	37.5			48.5		124
	ø9	R1/4	KFV12N-02S				17	26.6	23.6	41.2	35.7	15.5	8	46.7	38	90
		R3/8	KFV12N-03S				22			41.6	36.4			47.4		98
		R1/2	KFV12N-04S				22			44.8	37.5			48.5		123
		R1/4	KFV12B-02S				17			41.2	35.7			46.7		92
		R3/8	KFV12B-03S				22			41.6	36.4			47.4		100
		R1/2	KFV12B-04S				22			44.8	37.5			48.5		125

※Rねじのねじ込み後の参考寸法。

