MINI DAMPER HINGE HG-JHM9-S Side Mount



TORQUE HINGES

DAMPER HINGES

LIFT ASSIST HINGES

DETENT HINGES CONCEALED HINGES

BUTT HINGES

PIANO HINGES

STEP HINGES

LIFT-OFF HINGES

PIVOT HINGES

SPRING HINGES

CLEAN ROOM HINGES

HINGES FOR ALUMINIUM FRAME

DROP **HINGES**

GLASS DOOR HINGES

> SPECIAL HINGES



[Damper Working Direction]











Top-opening

Upward-opening Downward-opening Bottom-opening

[Front View] Cross-section



[Bottom View]



No.	Part Name	Material	Colour		
1	Body	POM			
2	Bracket R	DDT	Black, White		
3	Bracket L	PBT			
4	Damper	POM	_		

Hinge with	built-in damper.
Can he use	d for ton-onening

Can be used for top-opening, upward-opening, downward-opening and bottom-opening.

Under mount type also available.

[Specifications]

■Operating temperature: 0°C~40°C

[Applications]

Small lid for conference table, small cover of mechanical equipment, etc.

[Remarks]

Be sure to read the "Cautions"
2.



Sold in pairs. When installing, ensure that both hinge shafts are levelled and aligned.

[Recommended Screws]

Countersunk head screw M3, Binding head screw M3, Countersunk head tapping screw 3, Binding head tapping screw 3, etc.






Sasuga-kun

[Installation] Bracket	sa Sa
Rotation centre	thickness
Screw hole	5:4 PT 1:0 PT 1:

- X¹ Dimension when side board is flush with top surface of lid.
- $\ensuremath{\mathrm{\%^2}}$ To increase the opening angle of lid, rotate the stopper then fix it.

[Cut Out Dimensions]



Bracket for side mount

RoHS	CAD	Item Code	Item Name	Colour	Torque N·m/pair	Torque kgf·cm/pair	Opening Angle	Weight (g)	Box (pairs)	Carton (pairs)
G'	3D	170-025-895	HG-JHM9-S-BL	Black	0.054~0.086	0.55~0.88	105°	29	40	440
G	3D	170-025-896	HG-JHM9-S-WT	White				28	40	440
G	3D	170-037-326	HG-JHM9-S4-BL	Black	0.027~0.043	0.275~0.44		26	40	440
G'	3D	170-037-327	HG-JHM9-S4-WT	White				26	40	440

Refer to 1 : P.109, 2 : P.43