
SPRING HINGE ST150-6314-05








[How to Adjust Spring Tension]





remove the pin.

Item Code

170-022-486

CAD

RoHS

G 3D


Adjust spring tension with three steps. Put the pin to the hole and fix.

Spring loaded for self-closing.

- Spring tension adjustable with three steps with a hex key.
- Can reduce clearance between door and frame without door
- Aluminium hinge also available by made to order.

[Remarks]

In case of noise, apply lubricant (grease) to washer and torsion spring.



The value in case of door width 1000mm or less

Load Capacity

kgf/3 pcs%

TORQUE HINGES

DAMPER

HINGES LIFT ASSIST

HINGES DETENT

HINGES

CONCEALED

BUTT HINGES

PIANO HINGES

STEP HINGES

Weight Box

(g) (pcs)

336

LIFT-HINGES

PIVOT HINGES

SPRING HINGES

CLEAN ROOM

HINGES HINGES FOR

ALUMINIUM FRAME

DROP HINGES

GLASS DOOR HINGES

SPECIAL HINGES

Figure below shows the case of left-hanging. Right-hanging is symmetrical.

Item Name


ST150-6314-05


ALUMINIUM SPRING LIFT-OFF HINGE PM120

ssed 250,000 ope

close private cycle test

Special Colours (made to order)





Material

Stainless Steel (SUS304)

Spring loaded for self-closing.

Load Capacity

kgf/2 pcs%

40

- Spring tension adjustable with three steps with a hex key.
- Easy to remove the door.
- Black, white, golden or bronze colours and R10 corner rounding also available by made to order.

Load Capacity

N/3 pcs *

588

Please contact your local agent or your nearest Sugatsune subsidiary for detail/availability.

Load Capacity

N/2 pcs%

392

Finish

Plain


In case of noise, apply lubricant (grease) to washer and torsion spring. 8×φ5.3 φ10


[How to Adjust Spring Tension]

PM120-524401L


remove the pin.

Figure below shows the case of left-hanging.






PM120-BK-5243-09R




Spring tension

Middle

Door



hung on the right (viewing from the side of pulling the door).



Left-handed type. After the door is closed, leaves are not parallel to each other.

RoHS	CAD	Item Code	Item Name	Туре	Material	Finish	Door Width	Load Capacity N/2 pcs	Load Capacity kgf/2 pcs	Load Capacity N/3 pcs	Load Capacity kgf/3 pcs	Weight (g)	Box (pcs)
G'	3D	170-022-484	PM120-524401L	Left-handed	Alloy	Anodised	Max. 1000	200	20	300	30	172	2
G'	ЗD	170-022-485	PM120-525401R	Right-handed									2
G	_	170-048-791	PM120-BK-5243-09L	Left-handed		Black							2
G"	_	170-048-792	PM120-BK-5253-09R	Right-handed									2

Please contact your local agent or your nearest Sugatsune subsidiary for detail/availability.