
MAGNETIC RUBBER SHEET KMS Strong Force Type





RoHS	CAD	Item Code	Item Name	Material	W	t	Magnetic Force N/cm ²	Magnetic Force gf/cm ²	Weight (g)	Box (pcs)	Carton (pcs)	
G	ЗD	140-059-474	KMS-1-1000		12.7				42	100	-	
G'	ЗD	140-059-475	KMS-2-1000		19.1	0.8	0.588	60	62	100	-	
G'	ЗD	140-059-476	KMS-3-1000	Ferrite/	25.4				83	100	-	
G'	ЗD	140-059-453	KMS-4-1000	CPE	12.7				73	100	-	
G'	3D	140-059-492	KMS-5-1000		19.1	- 1	1.5	0.931	95	110	100	-
ď	ЗD	140-059-493	KMS-6-1000		25.4					146	100	-

Refer to 1 : P.431

Easy to cut.

Easy to apply with glue.

[Remarks]

- Be sure to read the "Cautions"

 1.
- Don't use outside.
- Do not use in contact with steam, hot water and water. The cut surface may rust.
- Do not use for installing fragile or heavy items vertically.

MAGNETIC CATCHES

KNUCKLE CATCHES & TENSION CATCHES

TOUCH LATCHES

LEVER LATCHES

SLIDE / BARREL BOLTS

DRAW LATCHES


PUSH LOCK FASTENERS & KNOB FASTENERS

ALUMINIUM FRAME CORNER CONNECTORS

> DOOR DAMPERS

MAGNETIC RUBBER SHEET NMS Extra Strong Force Type





RoH	S CAD	Item Code	Item Name	Material	w	t	Magnetic Force N/cm ²	Magnetic Force kgf/cm ²	Weight (g)	Box (pcs)	Cartor (pcs)
G	30	140-021-209	NMS-1-200		12.7			-	10	100	_
G	3D	140-021-210	NMS-2-200	Neodymium/	19.1	0.8	3.8	0.39	16	100	-
G	3 D	140-021-211	NMS-3-200	Nitrile	25.4				21	100	_
G	3 D	140-021-212	NMS-4-200	Rubber	12.7				19	100	-
G	3 D	140-021-213	NMS-5-200	(NBR)	19.1	1.5	5.4	0.55	30	100	_
G	3D	140-021-214	NMS-6-200		25.4				39	100	_

Refer to 1 : P.463, 2 : P.431

- Easy to cut.
- Easy to apply with glue.
- •Ultra thin but strong magnetic force by using neodymium magnet.
- Weaker magnetic type (KMS 1) available.

[Remarks]

- Be sure to read the "Cautions"
- Don't use outside.
- Do not use in contact with steam, hot water and water. The cut surface may rust.
- Max. temperature: 80°C
- Do not use for installing fragile or heavy items vertically.

SEALED COUNTER PLATE MC-JMP45




- For resin coated magnetic catch.
- The couter plate coated with resin prevents rusting, dust and spark.
- Completely sealed, ideal for high corrosion environments such as kitchen and bath equipment.


[Remarks]

- Do not use in contact with steam, hot water and water.
 - And do not leave strongly acidic or basic detergents
- Coated with resin may decrease the magnetic force of the magnetic catch used together.Please check with actual item.

[Recommended Screws]

M4 screw, tapping screw nominal 4 (truss or binding head, SUS)





No.	Part Name	Material	Finish / Colour		
1	Body	PP	White, Black		
2	Body (Back Side)	PP	Blue		
3	Plate	Steel (SPCC)	Clear Zinc Chromate (Trivalent)		

RoHS	CAD	Item Code Item Name		Colour	Weight (g)	Box (pcs)	Carton (pcs)	
G	3D	140-050-122	MC-JMP45WT	White	70	100	1000	
G	3D	140-029-241	MC-JMP45BL	Black	7.3	100	1000	