490 N

905

## TWIN WHEEL CASTER FPU55P Plate Type



- Wheels are coated in elastomer which absorbs vibration and gives an extra smooth and guiet movement.
- With red indicator to show locked state.

## [Remarks]

- Push the stopper to handle. Red lock indicator means locked state
- The load capacities in the table below indicate the loads when moving on a smooth surface.



Caster bracket FA55-FIX 1 to lock swivel available

RoHS	CAD	Item Code	Item Name	Туре	Load Capacity N/pc	Load Capacity kgf/pc	Weight (g)	Box (pcs)	Carton (pcs)
G'	ЗD	200-133-288	FPU55PSR	With Brake	400		151	4	72
ď	3D	200-133-293	FPU55PR	Without Brake	490	50	146	4	72

Refer to 1 : P.903

# Lock indicator

Drawing above shows the model with brake.

No.	Part Name	Material	Finish/Colour
1	Body	PA	Black
2	Plate	Steel (SPCC)	Coloured Zinc Chromate
3	Wheel	PA + Elastomer (TPU)	Black
4	Cover	PA	DIACK
(5)	Stopper	] PA	Black + Red

HEAVY DUTY CASTERS

SINGLE CASTERS

CASTERS WITH LEVELLING GLIDES

BALL CASTERS

SLIDING DOOR ROLLERS

490 N

## TWIN WHEEL CASTER FPU55N Threaded Bolt Type



- Wheels are coated in elastomer which absorbs vibration and gives an extra smooth and quiet movement.
- With red indicator to show locked state.

### [Remarks]

- Push the stopper to handle.Red lock indicator means locked state.
- The load capacities in the table below indicate the loads when moving on a smooth surface.
- The threaded bolt has a dished dent at the upper end for N10 only.

RoHS	CAD	Item Code	Item Name	Туре	d	Load Capacity N/pc	Load Capacity kgf/pc		Box (pcs)	Carton (pcs)
G'	ЗD	200-133-289	☆FPU55N3SR	With Brake	W3/8			128	4	72
G'	3D	200-133-294	☆FPU55N3R	Without Brake	W3/8			123	4	72
G'	ЗD	200-133-290	FPU55N10SR	With Brake	M10	490	50	128	4	72
G	3D	200-133-295	FPU55N10R	Without Brake	MIIU	490	50	123	4	72
G	ЗD	200-133-291	☆FPU55N12SR	With Brake	M12			128	4	72
G'	ЗD	200-133-296	☆FPU55N12R	Without Brake	IVIIZ			123	4	72
☆Lir	☆Limited stock available. Please contact your local agent or your nearest Sugatsune subsidiary for detail/availability.									

Drawing above shows the model with brake.

No. Part Name		Material	Finish/Colour		
1	Body	PA	Black		
2	Threaded Bolt	Steel (SWCH)	Coloured Zinc Chromate		
3	Wheel	PA + Elastomer (TPU)	Black		
4	Cover	PA	ыаск		
(5)	Stopper	PA	Black + Red		

(46)-

## TWIN WHEEL CASTER FPU55S Insert Bolt Type



- Wheels are coated in elastomer which absorbs vibration and gives an extra smooth and guiet movement.
- With red indicator to show locked state.

## [Remarks]

- Push the stopper to handle.Red lock indicator means locked state.
- The load capacities in the table below indicate the loads when moving on a smooth surface.

## [Parts Included]

Socket




	_
Cut out dimensions	١,
(w/o using the socke	
(w/o using the socke	:U

RoHS	CAD	Item Code	Item Name	Туре	Load Capacity N/pc	Load Capacity kgf/pc	Weight (g)	Box (pcs)	Carton (pcs)		
G'	ЗD	200-130-911	FPU55SSR	With Brake	400	400	400		131	4	72
G'	ЗD	200-130-912	FPU55SR	Without Brake	490	50	126	4	72		

\*\*Limited stock available. Please contact your local agent or your nearest Sugatsune subsidiary for detail/availability.

## 490 N



Drawing above shows the model with brake.

No.	Part Name	Material	Finish/Colour		
1	Body	PA	Black		
(2)	Insert Bolt	Steel (SWCH)	Coloured Zinc Chromate		
3	Wheel	PA + Elastomer (TPU)	Black		
4	Cover	PΑ	DIACK		
(5)	Stopper	PA	Black + Red		
6	Socket	Steel (STKM)	Coloured Zinc Chromate		